

NoiseGuide for Office and Call Centre Noise



Features

- Continuously measures the noise levels
- Instant warning when levels are high
- Average background noise checks
- Instantaneous and longer average sound level warnings
- Data logging with software download

Applications

- Offices
- Call Centre and Open Plan
- Library
- School Study Rooms and Canteen
- Hospital

Overview

The NoiseGuide is for use in open-plan offices and call centres. It warns staff when their noise levels are too high and likely to be causing problems.

The main part lights up green to indicate that the noise levels are fine. If somebody starts to speak too loudly, or creates any other excessive noise, the NoiseGuide will light up yellow as a warning and then red.

The light bar at the bottom of the NoiseGuide indicates the average sound level over 15, 30 or 60 minutes, for controlling longer term background noise levels.

Office Noise



- Loud talking?
 - Shouting?
 - Singing and whistling?
 - Music?
-
- Reduce stress levels
 - Avoid conflict
 - Improve productivity

NoiseGuide for Office and Call Centre Noise

Specifications

Technical Specifications

Frequency Range	20Hz to 20kHz
Measuring Range	30dB to 120dB
Deviation	± 1.5dB
Freq. Weighting	A weighted
Time Weighting	Slow
Dynamic Range	90dB RMS
Light Settings	Configured through SoundEar software
Display Data	Slow, LAeq,15
USB Port	Micro USB for Power and PC Connection. USB memory stick for logging and configuration
Power Supply	5VDC, max 2.5W. Micro USB.
Internal Memory	16 MB, up to 90 days logging (extended with use of memory stick)
Real-Time Clock	Battery backed
Dimensions	5.25" x 2.75" x 2.75", 134 x 70 x 70 mm

Head Office

NoiseMeters Ltd
7 Jayes Park
Ockley
Surrey
RH5 5RR

Telephone **0845 680 0312**
Fax **0845 680 0316**

Email: info@noisemeters.co.uk
Support: support@noisemeters.co.uk

Web Sites

Main site:
<https://noisemeters.co.uk>

Product shortcut:
<https://noisemeters.co.uk/p/sengk1/>

Tech Support:
<https://support.noisemeters.com>